



### Shield Shed Felt Mineral - Heavy Duty

#### Use

Single layer bitumen felt for the roofs of non-habitable structures with a pitch at or above 20 degrees. Typically apex or pent garden sheds, kennels, and hutches.

#### Product Information

SHIELD Shed Felt Heavy Duty is a reinforced glass fibre base with a mineral finish that provides strength, flexibility and tear resistance whilst the bitumen provides waterproofing. (The mineral finish protects the bitumen from UV damage, and is coloured to create a pleasant finish).

#### Performance & Standard Composition

Composition:	Bitumen
Form:	Roll
Finish:	Mineral - Green / Black
Length:	10m
Width:	1m
Roll Weight:	35kg
Carrier:	Reinforce Fibreglass



#### Installation

##### MATERIAL HANDLING

**Handling:** Material should be unloaded and handled with care to avoid damage.

**Site Storage:** Material should be stored on its end, on a firm, level clean base protected from direct sunlight.

##### PRIOR TO COMMENCEMENT

Application must always follow good, safe working practice. Prior to commencing works it is advisable to assess the work area, irrespective of levels of competence, ensuring all works are being planned and undertaken in a safe, pragmatic manner. Temperature should be considered, with works being undertaken ideally at temperatures over 10 C. Avoid installing in wet or very cold weather.

##### PREPARATION

Before starting on the roofing works, the installer should ensure the surfaces receiving the Shield Shed Felt are clean and dry. All existing felt should be removed, and the structure should be checked for adequacy and strength prior to new work being done.

##### DURABILITY

Life expectancy of this product is up to 10 years when installed as per manufacturers guidelines.

#### Disclaimer

The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details. Shield Membranes reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice.

0207 740 9279 | [www.shieldmembranes.com](http://www.shieldmembranes.com) | [info@shieldmembranes.com](mailto:info@shieldmembranes.com)

**“You’re protected with Shield on your side”**

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.



# SHIELD MEMBRANES

“You’re protected with Shield on your side”



NFRC  
LEADING ROOFING EXCELLENCE

