



### ShieldFELT VENTShield

#### Use

As a loose laid membrane, the product is used to provide a controlled partial bond to a substrate when the subsequent layer is fully bonded in hot melt in a built-up waterproofing system.

#### Product Information

VENTShield is a perforated underlay membrane, consisting of a glass fibre carrier coated in a polymer modified bitumen, rather than the traditional oxidised bitumen.

It has a film finish on both sides and is characterised by 40mm diameter perforations, positioned at approximately 120mm apart throughout the roll.



#### Installation

##### MATERIAL HANDLING

**Handling:** Material should be unloaded and handled with care to avoid damages.

**Site Storage:** Material should be stored on end on a firm, level clean base protected from direct sunlight.

##### PRIOR TO COMMENCEMENT

Application must always follow good, safe working practice. Prior to commencing works it is advisable to assess the work area, irrespective of levels of competence, ensuring all works are being planned and undertaken in a safe, pragmatic manner. Temperature should be considered, with works being undertaken ideally at temperatures over 10 C. Avoid installing in wet or very cold weather.

##### PREPARATION

Before starting on the roofing works, the installer should ensure the surfaces receiving the VENTShield are clean and dry.

##### DURABILITY

Life expectancy of this product is up to 15 years when installed as per manufacturers guidelines.

#### Performance & Standard Composition

Composition:	Modified Bitumen
Form:	Roll
Finish:	Film/Film
Length:	30m
Width:	1m
Roll Weight:	30kg
Carrier:	Glass Fibre

#### Disclaimer

The evolution of new product design is continuous and information is subject to change without notice. Customers should check with the supplier to ensure that they have the latest details. Shield Membranes reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice.

0207 740 9279 | [www.shieldmembranes.com](http://www.shieldmembranes.com) | [info@shieldmembranes.com](mailto:info@shieldmembranes.com)

**“You’re protected with Shield on your side”**



# SHIELD MEMBRANES

“You’re protected with Shield on your side”



NFRC  
LEADING ROOFING EXCELLENCE

