

SHIELD MEMBRANES MASTIC ASPHALT TERRAZZO

PRODUCT INFORMATION

Shield Membrane Mastic Asphalt Terrazzo provides a durable, elegant look to any project. It is available in polished or course finishes and produced to meet ISO 9001 and 14001 quality assurance and environmental standards.

It is offered across all paving flooring elements with slip and skid-resistant properties.

Shield Membranes Mastic Asphalt Terrazzo are fully tested to the appropriate standards in the UK and CE marked in accordance with the latest legislation. The terrazzo is hard-wearing, strong and durable.



PROPERTIES

Technical Profile

DENSITY (approx)

2,100-2,150kg/m³

CURING TIME

Light Foot Traffic: Full Traffic:

30-50 Minutes 24 Hours

LAYING THICKNESS

15mm - to any thickness

LABORATORY TESTING

WATER VAPOUR PERMEABILITY

0.067% (gm/day)

COMPRESSIVE STRENGTH (5 DAYS)

BS EN 13892-2

20 N/mm²

Flash Point

< 300°C

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.



**SHIELD
MEMBRANES**

CALL US TODAY 020 7740 9279

SHIELD MEMBRANES

MASTIC ASPHALT TERRAZZO

DESCRIPTION

Appearance:	Various aggregates with black bitumen compound.
Manufacturing:	Sawn / Ground - Polished
Governing Manufacturing Standards:	All data where relevant to be establish in accordance with: BS EN 12697/20 : 2012, BS EN 12825 : 2001, BS EN 1339 : 2003

SPECIFICATION

Emission of Asbestos:	No content
External Fire Performance:	Deemed to satisfy. See commission decision 20000/553/EUCU
Reaction to fire:	Class A1

SITE WORKS

Coverage	2.77 no per m ²
----------	----------------------------

MANUFACTURING

Materials Control	To ISO 9001 & 14001
-------------------	---------------------

FURTHER INFORMATION

Cleaning & Maintenance	Cleaning & maintenance details are available on request.
Weathering	It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual units. This does not in any way affect the performance of the units.
Product Evolution	The evolution of the new product design is continuous and information is subject to change without notice. Customers should check the supplier to ensure that they have the latest details. Shield Membranes reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice.
Contact Us	For technical information on the design, specification and construction when utilising the product, contact the Technical Advisory Services Department on 020 7740 9279 or via email info@shieldmembranes.co.uk

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.



CALL US TODAY 020 7740 9279